

Product Name:

GP-GREEN ULTIMATE

Technical Data:

• Type :	5/16" tufted synthetic grass carpet, straight stitch pattern	
• Pile Content:	Polyethylene (UV resistant), Prime monofilament with Curly yarn	
• Primary Backing:	U.V.- stabilized primary backing	
• Secondary Backing:	latex compound with a base of styrene-butadiene, pervious to water 4 mm wide drainage holes every 10 x 10 cm	
• Pile Height:	30 mm	+/- 10%
• Total Thickness:	33 mm	+/- 10%
• Stitch Per Metre	180	+/- 10%
• Number of tufts m ²	22680	+/- 10%
• Yarn Weight:	2301 g/m ²	+/- 10%
• Weight Primary backing:	142 g/m ²	+/- 10%
• Weight Secondary backing:	800 g/m ²	+/- 10%
• Total Weight:	3243 g/m ²	+/- 10%
• Roll Width:	Up to 4 m	+/- 5 cm
• Roll Length:	Please enquire	
• Tuft Bond Strength:	≥ 30 Newton	

TEST RESULTS

- Water permeability: tested unfilled: +/- 60 L/m²/min
- Colour fastness: Xenon test: blue scales ≥ 7, grey scales ≥ 4

LINE SYSTEMS

- NO

COLOUR OF THE CARPET/ YARN THICKNESS:

- Field Green & Brown/Green Curly
- Prime monofilament yarn – 140 µm (+/-10%); Curly yarn – 145 µm (+/-10%)

INFILL:

- N/A

PRODUCT APPLICATION

- Landscaping

INSTALLATION:

- Can be laid directly onto shock pad
- Loose-lay & adhesion of the seams to the underlying tape or with sewed seams. It is not recommended to install the carpet at temperatures below 10°C.
- Adhesive to be used: a solvent-free two compound reaction adhesive with a base of PU